§ 22.921 911 call processing procedures; 911-only calling mode.

Mobile telephones manufactured after February 13, 2000 that are capable of operating in the analog mode described in the standard document ANSI TIA/EIA-553-A-1999 Mobile Station-Base Station Compatibility Standard (approved October 14, 1999—available for purchase from Global Engineering Documents, 15 Inverness East, Englewood, CO 80112), must incorporate a special procedure for processing 911 calls. Such procedure must recognize when a 911 call is made and, at such time, must override any programming in the mobile unit that determines the handling of a non-911 call and permit the call to be transmitted through the analog systems of other carriers. This special procedure must incorporate one or more of the 911 call system selection processes endorsed or approved by the

[67 FR 77192, Dec. 17, 2002]

§22.923 Cellular system configuration.

Mobile stations communicate with and through base transmitters only. Base transmitters communicate with mobile stations directly or through cellular repeaters. Auxiliary test stations may communicate with base or mobile stations for the purpose of testing equipment.

§ 22.925 Prohibition on airborne operation of cellular telephones.

Cellular telephones installed in or carried aboard airplanes, balloons or any other type of aircraft must not be operated while such aircraft are airborne (not touching the ground). When any aircraft leaves the ground, all cellular telephones on board that aircraft must be turned off. The following notice must be posted on or near each cellular telephone installed in any aircraft:

"The use of cellular telephones while this aircraft is airborne is prohibited by FCC rules, and the violation of this rule could result in suspension of service and/or a fine. The use of cellular telephones while this aircraft is on the ground is subject to FAA regulations."

§22.927 Responsibility for mobile sta-

Mobile stations that are subscribers in good standing to a cellular system, when receiving service from that cellular system, are considered to be operating under the authorization of that cellular system. Cellular system licensees are responsible for exercising effective operational control over mobile stations receiving service through their cellular systems. Mobile stations that are subscribers in good standing to a cellular system, while receiving service from a different cellular system, are considered to be operating under the authorization of such different system. The licensee of such different system is responsible, during such temporary period, for exercising effective operational control over such mobile stations as if they were subscribers to it.

§ 22.929 Application requirements for the Cellular Radiotelephone Service.

In addition to information required by subparts B and D of this part, applications for authorization in the Cellular Radiotelephone Service contain required information as described in the instructions to the form. Site coordinates must be referenced to NAD83 and be correct to ± 1 second.

- (a) *Administrative information*. The following information is required either by FCC Form 601, or as an exhibit:
- (1) Location description; city; county; state; geographical coordinates correct to ± 1 second, the datum used (NAD 83), site elevation above mean sea level, proximity to adjacent market boundaries and international borders;
- (2) Antenna height to tip above ground level, the height of the center of radiation of the antenna above the average terrain, the height of the antenna center of radiation above the average elevation of the terrain along each of the 8 cardinal radials, antenna gain in the maximum lobe, the beamwidth of the maximum lobe of the antenna, a polar plot of the horizontal gain pattern of the antenna, the electric field polarization of the wave emitted by the antenna when installed as proposed: